

STREET DRAINS



STREET DRAINS

Products containing a dry anti-odour dry flap are designed primarily for outdoor installation.

Street drains equipped with an anti-odour water level are mainly used in the interior of buildings. And the version of the drain with the NEPTUNE float is intended primarily where it prevents possible penetration of odors from the sewer into the interior





- ✓ load capacity K3 (300 kg)
- ✓ load capacity L15 (1 500 kg)
- ✓ load capacity B 125 (12 500 kg)
- ✓ UV stabilized
- ✓ water resistance up to 90 °C
- ✓ in compliance with EN 1253
- ✓ in compliance with EN 124
- ✓ possibility of connecting waterproofing foil



BOTTOM STREET DRAIN, OUTLET D160/D110-250 WITH PLASTIC/CAST IRON GRID

Made of PP and PS, UV stabilized, and from grey cast iron DIN 1691. Load capacity compliant to EN 124-B 125 (12,500 kg) and a plastic grid made from polypropylene compliant to EN 1253 L15 (1,500 kg). Temperature resistance up to 90°C.

💧 **Flow rate (dry flap):** 250 l/min

PART NUMBER NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	ANTI-ODOUR PROTECTION	SAFETY SCREWS
 <p>328 KVS 160 S Li</p>	1/48	7,35	dry flap	-
 <p>328 z KVS 160 S Li z</p>	1/48	7,00	dry flap	✓
 <p>328 P KVS 160 S P</p>	1/48	1,96	dry flap	-
 <p>328 Pz KVS 160 S P z</p>	1/48	1,98	dry flap	✓