















## UNIVERSAL FLOOR DRAIN, SIDE OUTLET DN40 WITH PLASTIC/STAINLESS STEEL FRAME, COLLAR/FLANGE

The floor drain is designed for indoor and outdoor installations. The packaging includes a dry flap and an anti-odour water level. Made from polypropylene and stainless steel DIN 1.4301. Load capacity K3 (300 kg). Temperature resistance up to 90°C. Tested in compliance with EN 1253.

- Flow rate (dry flap): 56-70 l/min
- Flow rate (water level): 25-32 l/min

		PART NUMBER NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	STAIN-LESS STEEL FRAME	FLANGE
		<b>L1 382 A</b> L1PVBU 40	8/160	0,80	-	-
		<b>L1 382 B</b> L1PVBU 40 PR	8/160	0,98	-	✓
		<b>L1 382 N A</b> L1PVBU 40 N	8/160	0,83	✓	-
		<b>L1 382 N B</b> L1PVBU 40 N PR	8/160	1,01	✓	✓
		<b>F1 382 A</b> F1PVBU 40	8/160	0,78	-	-
		<b>F1 382 B</b> F1PVBU 40 PR	8/160	0,97	-	✓
		<b>F1 382 N A</b> F1PVBU 40 N	8/160	0,81	✓	-
		<b>F1 382 N B</b> F1PVBU 40 N PR	8/160	0,99	✓	✓
		<b>G1 382 A</b> G1PVBU 40	8/160	0,80	-	-
		<b>G1 382 B</b> G1PVBU 40 PR	8/160	0,98	-	✓
		<b>G1 382 N A</b> G1PVBU 40 N	8/160	0,82	✓	-
		<b>G1 382 N B</b> G1PVBU 40 N PR	8/160	1,00	✓	✓
		<b>382 A</b> PVBU 40	8/160	0,77	-	-
		<b>382 B</b> PVBU 40 PR	8/160	1,04	-	✓
		<b>382 N A</b> PVBU 40 N	8/160	0,79	✓	-
		<b>382 N B</b> PVBU 40 N PR	8/160	0,97	✓	✓
		<b>382 E</b> PVBU 40 4	8/160	1,25	✓	-
		<b>382 F</b> PVBU 40 PR4	8/160	1,46	✓	✓
Type C 	Type S 	<b>C 382 A</b> CPVBU 40	8/160	0,82	✓	-
		<b>C 382 B</b> CPVBU 40 PR	8/160	1,09	✓	✓
		<b>S 382 A</b> SPVBU 40	8/160	0,98	✓	-
		<b>S 382 B</b> SPVBU 40 PR	8/160	1,19	✓	✓
Type C1 	Type S1 	<b>C1 382 A</b> C1PVBU 40	8/160	0,93	✓	-
		<b>C1 382 B</b> C1PVBU 40 PR	8/160	1,15	✓	✓
		<b>S1 382 A</b> S1PVBU 40	8/160	1,12	✓	-
		<b>S1 382 B</b> S1PVBU 40 PR	8/160	1,33	✓	✓